

March 13, 2024

P-RFQ No. 2024-038

REQUEST FOR QUOTATION

SUPPLY AND DELIVERY OF VARIOUS CONSTRUCTION TOOLS AND MATERIALS (WR-2023-12-036, WR-2024-01-007, 02-020, 022)

The Santa Maria Water District (SMWD) hereinafter referred to as "the Purchaser", through its Bids and Awards Committee (BAC), invite interested parties to submit price quotation for the project, "**SUPPLY AND DELIVERY OF VARIOUS CONSTRUCTION TOOLS AND MATERIALS**" through Small Value Procurement (Sec. 53.9 of R.A. No. 9184) with Approved Budget for the Contract (ABC) of One Hundred Seventy-Three Thousand One Hundred Eighty-Three Pesos and Eighty Centavos Only (₱173,183.80).

	Description	Qty	Unit	Unit Cost	Total Amount
1	ADJUSTABLE WRENCH 10	2	PC		
2	ALLEN WRENCH	2	SET		
3	CABLE TIE NO.12	5	PACK		
4	CABLE TIE NO.4	5	PACK		
5	CABLE TIE NO.8	5	PACK		
6	CHAIN	10	MTR		
7	COMBINATION WRENCH TOOL SET	2	SET		
8	DIGITAL CLAMP METER	2	SET		
9	DIGITAL MULTI METER	2	UNIT		
10	ELECTRICAL PLIER	2	PC		
11	ELECTRICAL UTILITY TOOL SET	1	SET		
12	EXTENSION WHEEL	1	PC		
13	FLASHLIGHT RECHARGEABLE	20	PC		
14	HEAT GUN	1	PC		
15	НООК	52	PC		
16	LONG NOSE 6	2	PC		
17	METAL SCREW NO. 10	5	PC		
18	METAL SCREW NO. 5	5	PC		
19	PENETRATING OIL SPRAY	4	CAN		

"YOUR WATER OUR OBLIGATION YOUR CONVENIENCE, OUR SERVICE"



20	PHILLIPS SCREW DRIVER 5	2	PC	
21	PIPE WRENCH 12	3	PC	
22	PIPE WRENCH 14	2	PC	
23	PORTABLE DRILLER	1	UNIT	
24	PRECISION TOOL SET	1	SET	
25	PURE NICKLE PLATE	4	PC	
26	RAKE	3	PC	
27	SCREW DRIVER FLAT 5	2	PC	
28	SCREW DRIVER FLAT 6	2	PC	
29	SEALANT GUN	1	PC	
31	SHOVEL FLAT	1	PC	
31	SHOVEL POINTED	1	PC	
32	SOLDERING IRON SET	1	SET	
33	SPATULA	4	PC	
34	VISE GRIP CR 10	2	PC	
35	WARNING TAPE	1	PC	
	*** nothing follows ***			
	*** please see attached specifications***			

All items listed under the purchaser's specifications must be complied on a pass-fail basis.

Failure to meet any one of the requirements will result to rejection.

Likewise, it is understood that Purchaser's specifications are minimum requirements. The Bidder/Supplier may offer higher specifications or additional items, if any.

Procurement procedures will be conducted in accordance with the provisions of the Implementing Rules and Regulations (IRR) of Republic Act No. 9184 (Government Procurement Reform Act).

It is the intent of the Purchaser to evaluate the quotation for the item and award will be made to the quotation resulting in the overall lowest cost, meeting purchaser's technical specifications.

Likewise, in accordance with Section 54.6 and Appendix A of Annex "H" (Consolidated Guidelines for the Alternative Methods of Procurement) of the IRR of RA No. 9184, the supplier shall provide the following documentary requirements as a **condition for award** of the contract. The documents shall be attached together with the quotations.

"YOUR WATER, OUR OBLIGATION YOUR CONVENIENCE, OUR SERVICE"





- 1. PhilGEPS Registration Number
- 2. Mayor's/Business Permit
- 3. Photo Copy of Sample Official Receipt (OR)
- 4. Certificate of Registration (BIR FORM 2303);
- 5. Duly Notarized Omnibus Sworn Statement.

Your prices must be quoted in Philippine Peso and must include the unit price and total price, inclusive of all taxes to be paid and other incidental cost to the delivery site if the contract is awarded.

Payment shall be through check and advance payment is not allowed. Payment shall only be made upon completion of delivery of all items.

All quotations may be typewritten or handwritten and may be placed in sealed envelope marked "**SUPPLY AND DELIVERY OF VARIOUS CONSTRUCTION TOOLS AND MATERIALS**" (RFQ No. 2024-038) and must be submitted on or before **March 20, 2024, 11:00AM** at the SMWD main office. It may also be sent thru email on our official email address at <u>smwdbulacan@yahoo.com</u> on the specified time stated above and address to the **BAC Chairperson, Maria Leonora S. Romarate.**

Quotations shall be valid for thirty (30) calendar days from the deadline of submission of the same.

The delivery period shall be within **5 Days** from receipt of the Purchase Order (PO). The supplier should inform the purchaser at least two (2) days before the date of delivery. The Purchaser shall have the right to reject or to return the items that will be declared defective. The delivery will be made only during working days from 8:00 AM to 5:00 PM.

DELIVERY SITE: General Services Division of SMWD located at 301 J. P. Rizal St., Dulong Bayan, Santa Maria, Bulacan.

The prospective supplier shall submit the following:

- a) Duly accomplished Quotation Form; and
- b) Brochures of the items offered, if any.

The Santa Maria Water District reserves the right to accept or reject any quotation, and to annul the procurement process and reject all quotations at any time prior to Contract award, without thereby incurring any liability to the affected supplier or suppliers. SMWD also reserves the right to waive any required formality in the proposals received, and select the proposal which it determines to be the most advantageous to the government.

Prepared by:

Noted by:

Sgd.

Romel P. Lazaga Procurement Assistant Maria Leonora S. Romarate BAC Chairperson

Sgd.

YOUR WATE'R OUR OBLIGATION

YOUR CONVENIENCE, OUR SERVICE*





	ITEM	SPECIFICATION	REMARKS
,	Calif. T. M. A	NYLON CABLE TIE (black)	NYLON CABLE TIE 100 PCS PER PACK
1	Cable Tie No. 4	100 PCS per pack	100 PCS PER PACK
-+		4" (2.5 x 100mm)	111
2	Cable Tie No. 8	NYLON CABLE TIE (black) 100 PCS per pack	
2	cable fieldo. a	8" Heavy Duty (4.8 x 200mm)	
		NYLON CABLE TIE (black)	Martin Anna Martin
3	Cable Tie No. 12	100 PCS per pack	a subscription of
		12" Heavy Duty (4.8 x 300mm)	
		Lumen: 800LUMEN	
		 Body Material: Aluminum Alloy 	
		•LED : Cree LED	
		Switch Mode: High/Middle/Low/Strobe/SOS	A Non
		Color: BLACK	
		 Certification:CCC ,RoHS,ce,FCC 	C C C C C C C C C C C C C C C C C C C
		 Beam Distance: 90m 	A CONTRACTOR OF THE OWNER OF THE
4	Flashlight Rechargeable	 Charger: charge battery directly 	
0.00	indimight needed bedole	 Water resistant: IP65,2 meter under water 	
· .		 Battery Type:only 18650(included) 	~
		•Wattage: 10W	
		 Intensity: N8F-6800cd/N81-2000cd 	
		•Run Time:100 Hours	
		Drop Resistant:1M	
		•Size:116.6*26.4mm	1 _ 5
		•Weight: 66g(None Include Beattery)	
		12-inch (300 mm) pipe wrenches are ideal for pipe diameters of	
		1/2 inch (13 mm) to 1-1/2 inch (40 mm) with a pipe capacity of	
		up to 2 inches (50 mm)	
		Heavy-duty RIDGID pipe wrenches comply with federal	
4221		specifications GGG-W65IE, Type II, Class A	
5	PIPE WRENCH 12	Plumbing wrench features self-cleaning threads with easily	
		replaceable hook jaw, heel jaw and spring assembly	
		Durable ductile-iron housing and I-beam handle for exceptional	
		strength and longevity	ALV?
		Designed with a full floating forged hook jaw for superior	
		gripping and quick adjustments	
		Straight Pipe Wrenches have a sturdy, ductile-iron housing and	1 er
		an I-beam handle with a full floating forged hook jaw, featuring	8
		self-cleaning threads with replaceable hook and heel jaws.	
		Heavy-duty pipe wrenches comply with federal specifications	
6	PIPE WRENCH 14	GGG-W65IE, Type II, Class A.	
		Catalog No. 31020	
		Nominal Size: 14 inches (350mm)	
		Pipe Capacity: 2 inch (50mm)	
		Weight: 3 1/2 lb (1.6kg)	
		Weight. 5 1/2 ib (1.0kg)	
\rightarrow		Weight: 5 1/2 in (1.0kg)	
-		Weight: 5 1/2 in (1.6kg)	
		Cap Hook Screw	é
7	ноок	Cap Hook Screw PVC Coated	Comin
7	ноок	Cap Hook Screw	Game
7	ноок	Cap Hook Screw PVC Coated	Gamin
7	ноок	Cap Hook Screw PVC Coated 2"	Game
7	ноок	Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds	Gamin
7	ноок	Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds Handle Material :Alloy Steel	Game
7	ноок	Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds Handle Material :Alloy Steel Flexible :No	Gamesia
7	ноок	Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds Handle Material :Alloy Steel Flexible :No Overall Length :10.0	Gumesia
7	ноок	Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds Handle Material :Alloy Steel Flexible :No Overall Length :10.0 Size :0 in - 1.312 in	G
7	ноок	Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds Handle Material :Alloy Steel Flexible :No Overall Length :10.0	Como
7	ноок	Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds Handle Material :Alloy Steel Flexible :No Overall Length :10.0 Size :0 in - 1.312 in ANSI Specification :Meets or Exceeds	G
7	ноок	Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds Handle Material :Alloy Steel Flexible :No Overall Length :10.0 Size :0 in - 1.312 in ANSI Specification :Meets or Exceeds Packaging :Carded	Come
8	HOOK	Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds Handle Material :Alloy Steel Flexible :No Overall Length :10.0 Size :0 in - 1.312 in ANSI Specification :Meets or Exceeds Packaging :Carded Weight (Catalog) :1.06	0
		Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds Handle Material :Alloy Steel Flexible :No Overall Length :10.0 Size :0 in - 1.312 in ANSI Specification :Meets or Exceeds Packaging :Carded Weight (Catalog) :1.06 Warranty :Full Lifetime	Comin
		Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds Handle Material :Alloy Steel Flexible :No Overall Length :10.0 Size :0 in - 1.312 in ANSI Specification :Meets or Exceeds Packaging :Carded Weight (Catalog) :1.06 Warranty :Full Lifetime Jaw Thickness :.4	Comin
		Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds Handle Material :Alloy Steel Flexible :No Overall Length :10.0 Size :0 in - 1.312 in ANSI Specification :Meets or Exceeds Packaging :Carded Weight (Catalog) :1.06 Warranty :Full Lifetime Jaw Thickness :.4 Jaw Width :2.9	Comin
		Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds Handle Material :Alloy Steel Flexible :No Overall Length :10.0 Size :0 in - 1.312 in ANSI Specification :Meets or Exceeds Packaging :Carded Weight (Catalog) :1.06 Warranty :Full Lifetime Jaw Thickness :.4 Jaw Width :2.9 Jaw Size Scale :Yes Finish :Satin Chrome with Polished Face Overall Height :0.75	Comin
		Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds Handle Material :Alloy Steel Flexible :No Overall Length :10.0 Size :0 in - 1.312 in ANSI Specification :Meets or Exceeds Packaging :Carded Weight (Catalog) :1.06 Warranty :Full Lifetime Jaw Thickness :.4 Jaw Width :2.9 Jaw Size Scale :Yes Finish :Satin Chrome with Polished Face Overall Height :0.75 UPC :037103254009	Commin
		Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds Handle Material :Alloy Steel Flexible :No Overall Length :10.0 Size :0 in - 1.312 in ANSI Specification :Meets or Exceeds Packaging :Carded Weight (Catalog) :1.06 Warranty :Full Lifetime Jaw Thickness :.4 Jaw Width :2.9 Jaw Size Scale :Yes Finish :Satin Chrome with Polished Face Overall Height :0.75 UPC :037103254009 Overall Width :3.0	Como
		Cap Hook Screw PVC Coated 2" ASME Specification :Meets or Exceeds Handle Material :Alloy Steel Flexible :No Overall Length :10.0 Size :0 in - 1.312 in ANSI Specification :Meets or Exceeds Packaging :Carded Weight (Catalog) :1.06 Warranty :Full Lifetime Jaw Thickness :.4 Jaw Width :2.9 Jaw Size Scale :Yes Finish :Satin Chrome with Polished Face Overall Height :0.75 UPC :037103254009	Comin

		1	
9	PORTABLE DRILLER	 * Next-level compactness with strong performance and brushless motor * Easy handling and operation due to compact design * High-efficiency brushless motor extends work hours and tool life * Maximum performance and efficiency with working speed of up to 1,900 rpm * Optimal for screwdriving in wood or drilling in wood and metal in narrow spaces INCLUSIONS: 1 x Brushless Cordless Drill Driver 18V; 1 x Carrying Case; 1 x 23pcs. Accesories; 2 x Battery GBA 18V 2.0Ah (spare part number 1 617 B00 0BJ); 1 x Charger GAL 18V-20 Professional 1 600 A02 1KT; 	
10	DIGITAL CLAMP METER	$\begin{tabular}{lllllllllllllllllllllllllllllllllll$	
11	DIGITAL MULTI METER	Maximum voltage between any terminal and earth ground600. V SafetylEC 61010-1: Pollution Degree 2 IEC 61010-2-033: CAT III 600V Fuse for A input11 A, 1000 V FAST Fuse (Fluke PN 803293) DisplayDigital: 6,000 counts, updates 4 per second Bar graph33 segments, updates 32 per second Operating temperature-10°C to +50°C Storage temperature-40°C to +60°C Battery type9 volt Alkaline, IEC 6LR61 Battery life400 hours typical, without backlight Accuracy Specifications DC millivoltsRange/resolution600.0 mV / 0.1 mV Accuracy \pm [[% of reading] + [counts]): 0.5% + 2 DC voltsRange/resolution6.000 V / 0.001 V 60.00 V / 0.01 V 60.00 V / 0.1 V Accuracy \pm [[% of reading] + [counts]): 0.5% + 2 Auto voltsRange/resolution600.0 V / 0.1 V Accuracy \pm [[% of reading] + [counts]): 0.5% + 2 Auto voltsRange/resolution600.0 V / 0.1 V Accuracy \pm [[% of reading] + [counts]): 0.5% + 2 Auto voltsRange/resolution600.0 V / 0.1 V Accuracy \pm [[% of reading] + [counts]]: 0.5% + 2 Auto voltsRange/resolution600.0 V / 0.1 V Accuracy1.0% + 3 (DC, 45 Hz to 500 Hz) 2.0% + 3 (500 Hz to 1 kHz) AC wolts ¹ True RMSRange/resolution6.000 V / 0.01 V 60.00 V / 0.01 V	

12	VICE GRIP CR 10	10" 10R Straight (84-371) Induction hardened jaws last longer and grip better than non- induction hardened jaws Adjustment screw provides the ideal holding pressure Built-in wire cutter Forged steel is strong and durable	
13	RAKE	Flat Carbon Steel Heavy Duty Dimension (WxLxH): 8x37x121cm	1
14	ALLEN WRENCH	Heat treated chrome vanadium steel shafts with a polished satin finish Extra-Long arm allows extra torque to be applied to the fixing One side of the wrench comes with ball hex keys that can be deflected within 30 degrees from being parallel to the screw head Sizes: 1.5,2,2.5,3,4,5,6,8, and 10mm Plastic holder with numbered wrench sizes Made of heat treated chrome vanadium steel Allen hex shaft, second side with ball head Set includes a plastic foldable holder	States and a state of the state
15	ELECTRICAL PLIER	Size: 200mm(L) Dimensions width=11 height=2 length=28.2 Weight 0.45 kgs	Care - Care
16	PRECISION TOOL SET	set with star screw, ergonomic handle, and grip Mounting Type; Multifunctional Combo KitNumber of pieces included; 24Material: chrome vanadium alloy steelHead type; square head, Y type, cross, one word, plum type, hexagonal type, star type, rice typeWeight; 128 (grams)scope of applicationPrecision instruments, mobile phones, tablets, computers, watches, glasses, cameras, game consoles, chassis, circuits and other maintenance equipment.	
17	ELECTRICAL UTILITY TOOL SET	Contains: 1/2" Drive 6-Point Sockets : 10, 11, 12, 13, 14, 17, 19, 22, 24mm 1/2" Drive Ratchet 10" Long 1/2" Drive Extensions: 5" & 10" Long Open End Wrenches: 11, 12, 13, 14, 17, 19mm Screwdrivers Slotted: 1/8", 5/32", 7/32", 1/4" Screwdrivers Phillips*: #0, #1, #2 Pliers: 6 ¾" Side Cutter, 7 3/8" Linesman, 8 3/8" Long Nose. Lockable storage case provides proper storage and access. 2 removable foam organizers with size imprinting on the socket, wrench, and screwdriver tool cutouts	
18	LONG NOSE 6	8 in Long Nose Pliers 3-Zone bi-material grips for comfort and controlBlack oxide finish helps resist corrosionDrop-forged steel for strength and durability	
19	PHILLIPS SCREW DRIVER 5	VANADIUM BLADES AND WITH TOUGH HARDENED BLACK OXIDE TIPS PHO 1/8" x 5"	

20	SCREW DRIVER FLAT 5	3/16 x 5" (5 x 125mm) Cushion grip phillips screwdriver is chrome plated which is corrosion resistant soft grip handle provides better comfort and its used for fastening nuts and bolts Bi-material(PP+TPR) soft grip handle providing excellent comfort Chrome vanadium(Cr-V) balde for durability Magnetic tips for easy pick up and screw locator Three-sided handle allowing more torque with anti-slip and anti- rolling features Ergonomic design with finger point in neck-down area for precise control Built-in-hang hole for easy storage Screw tip identification on the handle for faster accessibility"	3/16 X 4 IN 5 X 100 MM
21	SCREW DRIVER FLAT 6	3/16 x 6" (5 x 150mm) Cushion grip phillips screwdriver is chrome plated which is corrosion resistant soft grip handle provides better comfort and its used for fastening nuts and bolts Bi-material(PP+TPR) soft grip handle providing excellent comfort Chrome vanadium(Cr-V) balde for durability Magnetic tips for easy pick up and screw locator Three-sided handle allowing more torque with anti-slip and anti- rolling features Ergonomic design with finger point in neck-down area for precise control Built-in-hang hole for easy storage Screw tip identification on the handle for faster accessibility"	3/16 X 6 IN 5 X 150 MM
22	SEALANT GUN	HEAVY DUTY. 9" - 230MM. USE FOR SEALANT AND GLUE DISPENSER.	
23	SHOVEL FLAT	Y-Grip Handle - Comfortable handle and firm grip.Carbon Steel - For strength and durabilityRust and Scratches Its design to ensures good performance for digging in stony, clay and hard soils .Optimum Wrist Angle - Lifting angle of 26 degree designed for optimal digging performance Wood Handle LxWxH 18 x 5 x104 cm	
24	SHOVEL POINTED	Round Point Shovel Type High Quality Size: 9"W x 11-1/4"H Digging Scooping Transplating Trenching	
25	SPATULA	high quality putty knife *secure grip *stainless steel *flex blade	
26	CHAIN	8mm DIN766 MF Grade 40 Calibrated Anchor Chain	5 Sector Sectors

27	WARNING TAPE	Specifications Length: 300m Size: 7cm	CAUTION
28	COMBINATION WRENCH TOOL SET	-Made of Chrome Vanadium Steel -Both the open ended head and the ring are angled at 15° for optimum accessibility -Nickel chrome plating protects against corrosion -Anti-slip feature -Heavy-duty nylon pouch -8mm,9mm,10mm,12mm,13mm,14mm,17mm, 19mm,21mm,22mm, 24mm, 27mm, 30mm, 32mm	COMBINATION WRENCH SET
29	Penetrating Oil Spray	Appearance: Aerosol-Aerosolized Llquid Color: Light(or pale) amber	

1	Metal Crew No. 10	Sheet Metal Screw, Philips Drive Pan Head # 10	Part -
2	Metal Crew No. 5	Sheet Metal Screw, Philips Drive Pan Head # 5	
3	Pure Nickle Plate 100x100	100x100mm Pure Nickel Ni Sheet Plate For Electroplating Anode Element 1mm	
4	Heat Gun 220V 300W Heavy Duty	Heat Gun 220V 300W Heavy Duty	

1	Soldering Iron Set Adjustable Temperature; 60-80w 220v	Soldering Iron Kit, 80W Adjustable Temperature Welding Tool Kit, with LCD Display, 5 Soldering Tips, Desoldering Pump, Portable Repair Soldering Iron Tools	
2	Extension Wheel 15 meters length, 10amps, 220V	10amps, 220v-240v, on/off switch, LED indicator, Safety Thermal Cutoff, 15 meters extension lead, easy wind handle	

.